

CETO CIRCLET

CHANDELIER

Ceto Circlet captures the variation and rippling of the surface of the ocean. Each piece is mouth blown, reflecting a distinct pattern that emits a delicate luminosity, evoking the presence of the sea and its undulating movements. The Ceto Circlet collection features a circular band suspended in a horizontal plane, to which several Ceto lamps are affixed.

AVAILABLE FINISHES







CC1412 CC2015 38KG / 84LB 50KG / 110LB







FROSTED BLACK GLASS


ANODISED

ANODISED


TECHNICAL

MATERIAL	ANODISEE	ALUMINIUM, GLASS	CORD	3 X 3M / 9"	3 X 3M / 9'10" CLEAR COAXIAL CABLE		
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) CC809 - 17W, 2200-2450 LUMEN, 3000K CC1412 - 25W, 3450 LUMEN, 3000K CC2015 - 30W, 4370-5050 LUMEN, 3000K WATTAGE AND LUMEN OUTPUT WILL VARY SLIGHTLY DEPENDING ON CONSTANT CURRENT OUTPUT. DIMMING OPTIONS		SUSPENSION	3 X 3M / 9'10" Ø1.2MM STAINLESS STEEL WIRE			
				LONGER LENGTHS AVAILABLE UPON REQUEST			
220-240V REGIONS			CANOPY	Ø120 X 30MM CEILING CANOPY. CIRCULAR LINISH AND ANODISED TO MATCH THE SPECIFIED FINISH OF CETO. MOUNTING HOLES TO SUIT STANDARD 4" JUNCTION BOXES FOR THE US/CAN REGION.			
	· PHASE - DIMMING RANGE 5 - 100% · DALI - DIMMING RANGE 1 - 100%						
110-120V REGIONS	DIMMING OPTIONS DALI - DIMMING RANGE 0 - 100% O-10V - DIMMING RANGE 0 - 100% HOWN - DIMMING RANGE 0 - 100% PWM - DIMMING RANGE 0 - 100% RX - DIMMING RANGE 0 - 100% PUSH DIM - DIMMING RANGE 0 - 100% ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE. PLEASE CONTACT OUR STUDIO FOR FURTHER INFORMATION REGARDING MOST SUITABLE LAMPING TECHNOLOGY FOR YOUR SPECIFIC PROJECT/REGION.			AN OPTIONAL Ø170 X 40MM CEILING CANOPY IS AVAILABLE WHEN DRIVERS CANNOT BE HOUSED WITHIN A CEILING/WALL/SITE CAVITY.			
			PRODUCT CODES SKU	EG. CC809.G-BLK.A-BLK CETO 809 CIRCLET IN BLACK GLASS WITH A BLACK ANODISED BODY			
				CC809.G-XXX.A-XXX			
				GLASS	FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT) BLACK ANODISED (A-BLK) CHAMPAGNE ANODISED (A-CHM)		
			DIMENSIONS	VARIOUS SEE DIMENSIONS ON FOLLOWING PAGE*			
LED LIFESPAN	50,000 HRS		WEIGHT	CC809 CC1412 CC2015	23KG / 51LB 32KG / 70LB 42KG / 93LB		
IP RATING	IP20 - FOR INDOOR USE ONLY		PACKAGING	CC809	L90CM W	90CM H 35CM / L 2'11" W 2'11" H 1'2"	
CERTIFICATION	AU/NZ EU	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1		CC1412 CC2015		V 75CM H 35CM / L 3'3" W 2'6" H 1'2" V 75CM H 35CM / L 4'1" W 2'6" H 1'2"	
	US/CAN	ETL/UL CERTIFICATION PENDING	PACKAGING WEIGHT	CC809	27KG / 60L		


DIMENSIONS



CC809 Ø 980 H 200 RING Ø 800 Ø 3'3" H 7.9" RING Ø 2'75" MIN DROP HEIGHT - H 600 / 2'



CC1412 Ø 1575 H 200 RING Ø 1400 Ø 5'2" H 7.9" RING Ø 4'7" MIN DROP HEIGHT - H 900 / 2'11"



CC2015 Ø 2175 H 200 RING Ø 2000 Ø 7'2" H 7.9" RING Ø 6' 7" MIN DROP HEIGHT - H 1200 / 3'11"